



**Asian Electron Co., Ltd.**

6F-1, No.150, Jian Yi Road, Zhonghe Dist., New Taipei City 235, TAIWAN, R.O.C.

TEL: 886-2-8226-5158 FAX:886-2-82265150

<http://www.asian-electron.com>



# Quick Charger

## User Manual

## **Features:**

- 1, Compact 2-port USB Quick Charger, 5A output current.
- 2, Wide range output which is suitable for motive, car, bus etc.
- 3.The original USB cable must be used to ensure the same charging time as original.
- 4, It will not interfere with the devices in the car, such as GPS, Event Data Recorder and FM radio.
- 5, Independent power source, avoid any fails, short load.

## **Specification:**

Input voltage: DC 8~36V/2.5A

Output voltage: DC 5V (USB)

Output current: 5000mA

Size: 70 \* 43.9 \* 32mm

## **Suggestion:**

Firstly,uninstall the plaque in the cigarette plug,secondly weld the cord black & red onto the positive and negative of the cigarette plug separately, thirdly add the drivepipes one by one to insulate the wires.

## **Note:**

The red DC cable is Positive,  
The black DC cable is Negative,  
The fuse is 3A.

## **Optional:**

GPS. Event Data Recorder, 2pcs adapter cable(cigarette plug to USB), 1pc mico USB cable.

## **Warning:**

- 1, Please confirm if the output voltage of the cigarette plug is 5V before installation.
  - 2, Please do not forget to bush the connection after welding the cigarette plug and the wire (positive and negative) together, in order to insulate it.
- Only need to connect the red wire and black wire, and pls cut off the others.

## **Protection:**

1. OCP: Over Current Protection.
2. OVP:Over Voltage Protection.
3. OTP:Over Temperature Protection.
4. OPP: Over Power Protection.
5. SCP: Short circuit Protection.